


Dimensions			
Nominal (in)	ID (mm)	OD (mm)	Shipping Weight (kg/m)
10	250	288	12.6
12	300	345	15.4
15	375	430	20.0
18	450	520	24.5
21	525	605	31.0
19.5	490	565	27.6
24	600	690	34.9
27	685	775	39.6
30	750	865	45.1
33	840	940	49.1
36	910	1022	55.9
40	1020	1144	66.6
42	1070	1210	76.5
48	1210	1370	81.4
54	1370	1538	105.1
60	1520	1710	117.4
66	1680	1880	156.6
72	1830	2040	190.5

PROPRIETARY  
 NO PART OF THIS DOCUMENT MAY BE REPRODUCED, STORED IN A RETRIEVAL SYSTEM OR TRANSMITTED IN ANY FORM WITHOUT THE WRITTEN PERMISSION OF IDEAL PIPE

NOTE  
 DRAWING IS NOT DRAWN TO SCALE - INTENTIONALLY DRAWN TO EMPASIZE PROFILE DETAIL

THIRD ANGLE PROJECTION



DRAWN BY:  
AQ

DATE:  
26 Aug 2013

CHECKED BY:  
MK

DATE:  
30 Aug 2013

SCALE:  
N/A

MATERIAL:  
345646C

TITLE:  
Streamliner

DRAWING NO:  
Streamliner



IDEAL PIPE  
 1100 IDEAL DRIVE  
 THORNDALE, ONTARIO  
 NOM 2PO  
 PHONE: (519) 473-2669  
 FAX: (519) 641-2524  
<http://www.IdealPipe.ca/>

APPLICABLE STANDARDS:  
ASTM F894

STIFFNESS:  
160 / 250

REV:  
002